

Native Full HD High Resolution Electronic View Finder

DF-3515

HDR



Features

- 1920 x 1080 OLED
- HDMI Input Supporting All HDMI Enabled Cameras
- HDR Waveform and Range Highlight overlay **NEW**
- SDI Input Supporting All SDI Enabled Cameras
- Very Low Latency
- HDR Picture Display

Functions

- Peaking (For Critical Focus)
- Brightness/ Contrast/ Color Temperature/ Gamma/ Gain/ Offset Controls
- Inversion (UD)
- Auto/ Manual Sense of Segmented Frame or Interlace
- HDR Waveform and Range Highlight overlay with Scale and Color Setting
- Quick Menu Access
- Magnification For Focus Assistance (Off, 2x, 4x)
- Mono/ Blue Only View Mode
- Marker Selection (Center/ Frame/ 1.33:1/ 1.88:1/ 2.35:1/ 2.39:1/ 1.85:1)
- LED and On Screen Tally

Specifications

SDI Input

1920 x 1080/47.95p, 48p, 50p, 59.94p, 60p
1920 x 1080/50i, 59.94i, 60i
1920 x 1080/23.98p/sF, 24p/sF, 25p/sF, 29.97p/sF, 30p/sF
1280 x 720/23.98p, 24p, 25p, 29.97p, 30p, 50p, 59.94p, 60p

HDMI Input

1920 x 1080/47.95p, 48p, 50p, 59.94p, 60p
1920 x 1080/50i, 59.94i, 60i
1920 x 1080/23.98p, 24p, 25p, 29.97p, 30p
1280 x 720/23.98p, 24p, 25p, 29.97p, 30p, 50p, 59.94p, 60p
4K : 30p, 29.97p, 25p, 24p, 23.98p

Display

Color Depth	8 bits
Contrast	1,000,000 : 1
Resolution	1920(H) x 1080(V) Pixels

General specifications

Power Requirements	DC9-32V
Power Consumption	7 W
Operating Temperature Range	0 to 40°C
Operating Humidity Range	20 to 80%RH (No Condensation)
Dimensions	76.2(H) x 78(W) x 135(D) mm (Excluding Protrusions)
Weight	Approx. 0.4 kg

